eco guardians

Grease Guardian®
Sustainable Grease Management

GGX25 Grease Guardian PRO 230 VAC Specification

Front View



Right End View



Footprint/Containment area



GGX PRO Features:

- PRO - Extended Cleaning Cycle Feature with spray bar, audio alert and user "action" button.
- PRO - Daily Maintenance Audio alert.
- Automatic grease removal mechanism
- Internal dry solids strainer
- Grease heating system
- PLC controller with LCD notifications
- Energy saving mode
- Bidirectional Inlet and Outlet plumbing ports
- Quick Fit rubber couplings
- Pipework and power cabling concealed at rear.
- Warranty: Parts 1 year. Tank 5 years.

Exclusions:

- RCD, IP socket, or any electrical supply devices beyond mains cord/plug as supplied.
- Pipework beyond inlet/outlet couplings /ventilation piping

Options: by FM Environmental on request:

- Tank support frame
- Upstream coarse solids strainer modules
- Externally mounted blower system (for surface scum dispersal)
- Sample valve (150mm addtional length in outlet pipework required)

Key Installation Notes:
Allow for the minimum clearances shown, including clearance for pipe connections and user access to front of unit

Unit should be plumbed at a gravity fall (1:40 for maximum perfornance)

Control panel should be fully accessible to service personnel

Electrical supply is single phase. An RCD/ELCB rated 30mA must be installed for all Grease Guardian electrical supplies

Observe all local plumbing regulations for pipe venting, trapping.
Observe all local safety and hygiene regulations

Note: Not to be treated as an installation guide. Installation guide in full is issued on supply of system.

TECHNICAL DATA

Weight	38 kg (empty)
Material	Exterior, 16 gauge stainless steel, bright finish
Interior	Stainless Steel and Acetal Plastic Components
Tank Capacity	60 litres
Maximum Flow Rate	1.58 Litres per Second
Tank grease Retention Capacity	57.4 pounds/26 kg
Solid Strainer Capacity	6.6 pounds/2.99 kg
Skimming Rate	5 litres per hour
Progamming/Control	24 hour, 7 day, multi functional digital
Electrical Load	230VAC, 1025Watts, 4.46 AMPS

NSF C US
NSF ASME A112.14.3 ASME A112.14.4
PDI
MET C US

Copyright Januray 2026 FM Environmental Ltd. All Rights Reserved. Specification subject to change without notice.